

The US-CERT Cyber Security Bulletin provides a summary of new vulnerabilities that have been recorded by the National Institute of Standards and Technology (NIST) National Vulnerability Database (NVD) in the past week. The NVD is sponsored by the Department of Homeland Security (DHS) National Cyber Security Division (NCSD) / United States Computer Emergency Readiness Team (US-CERT). For modified or updated entries, please visit the [NVD](#), which contains historical vulnerability information.

The vulnerabilities are based on the [CVE](#) vulnerability naming standard and are organized according to severity, determined by the [Common Vulnerability Scoring System](#) (CVSS) standard. The division of high, medium, and low severities correspond to the following scores:

- [High](#) - Vulnerabilities will be labeled High severity if they have a CVSS base score of 7.0 - 10.0
- [Medium](#) - Vulnerabilities will be labeled Medium severity if they have a CVSS base score of 4.0 - 6.9
- [Low](#) - Vulnerabilities will be labeled Low severity if they have a CVSS base score of 0.0 - 3.9

Entries may include additional information provided by organizations and efforts sponsored by US-CERT. This information may include identifying information, values, definitions, and related links. Patch information is provided when available. Please note that some of the information in the bulletins is compiled from external, open source reports and is not a direct result of US-CERT analysis.

High Vulnerabilities				
Primary Vendor -- Product	Description	Discovered Published	CVSS Score	Source & Patch Info
ArcSoft -- MMS Composer	Multiple buffer overflows in ArcSoft MMS Composer 1.5.5.6, and possibly earlier, and 2.0.0.13, and possibly earlier, allow remote attackers to cause a denial of service (crash) or execute arbitrary code via crafted MMS (Multimedia Messaging Service) messages that trigger the overflows in the (1) M-Notification.ind, (2) M-Retrieve.conf (Header and Body), or (3) SMIL parsers.	unknown 2006-08-14	7.0	CVE-2006-4131 BUGTRAQ FULLDISC OTHER-REF OTHER-REF BID FRSIRT SECUNIA
Bob Jewell -- Discloser	Multiple PHP remote file inclusion vulnerabilities in Bob Jewell Discloser 0.0.4 and earlier allow remote attackers to execute arbitrary PHP code via a URL in the fileloc parameter to (1) content/content.php or (2) /inc/indexhead.php.	unknown 2006-08-17	7.0	CVE-2006-4207 OTHER-REF OTHER-REF BID XF
Boite de News -- Boite de News	PHP remote file inclusion vulnerability in boitenews4/index.php in Boite de News 4.0.1 allows remote attackers to execute arbitrary PHP code via a URL in the url_index parameter.	unknown 2006-08-14	7.0	CVE-2006-4123 Milw0rm BID XF
Chaussette -- Chaussette	Multiple PHP remote file inclusion vulnerabilities in Chaussette 080706 and earlier allow remote attackers to execute arbitrary PHP code via a URL in the _BASE parameter to (1) Classes/Evenement.php, (2) Classes/Event.php, (3) Classes/Event_for_month.php, (4) Classes/Event_for_week.php, (5) Classes/My_Log.php, and (6) Classes/My_Smarty.php.	unknown 2006-08-16	7.0	CVE-2006-4159 OTHER-REF BID FRSIRT SECUNIA
Chaussette -- Chaussette	PHP remote file inclusion vulnerability in Chaussette 080706 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the _BASE parameter to Classes/Event_for_month_per_day.php, a different vector than CVE-2006-4159. NOTE: the provenance of this information is unknown; the details are obtained from third party information.	unknown 2006-08-17	7.0	CVE-2006-4216 SECUNIA
Cisco -- PIX Firewall	** DISPUTED ** Unspecified vulnerability in Cisco PIX 500 Series Security Appliances allows remote attackers to send arbitrary UDP packets to intranet devices via unspecified vectors involving Session Initiation Protocol (SIP) fixup commands, a different issue than CVE-2006-4032. NOTE: the vendor, after working with the researcher, has been unable to reproduce the issue.	unknown 2006-08-16	7.0	CVE-2006-4194 OTHER-REF OTHER-REF OTHER-REF CISCO
CPG-Nuke -- Dragonfly CMS	Cross-site scripting (XSS) vulnerability in Dragonfly CMS 9.0.6.1 and earlier allows remote attackers to inject arbitrary web script or HTML via the search field.	unknown 2006-08-16	7.0	CVE-2006-4162 BUGTRAQ XF
David Kent Norman -- Thatware	PHP remote file inclusion vulnerability in config.php in David Kent Norman Thatware 0.4.6 and possibly earlier allows remote attackers to execute arbitrary PHP code via a URL in the root_path parameter.	unknown 2006-08-17	7.0	CVE-2006-4213 OTHER-REF FRSIRT XF
DConnect -- DConnect Daemon	Stack-based buffer overflow in main.c in DConnect Daemon 0.7.0 and earlier allows remote attackers to execute arbitrary code via a large nickname, which is not properly handled by the listen_thread_udp function.	unknown 2006-08-14	7.0	CVE-2006-4125 BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECTrack

				SECUNIA XF
Dolphin -- Dolphin	Multiple PHP remote file inclusion vulnerabilities in Dolphin 5.1 allow remote attackers to execute arbitrary PHP code via a URL in the dir[inc] parameter in (1) index.php, (2) aemodule.php, (3) browse.php, (4) cc.php, (5) click.php, (6) faq.php, (7) gallery.php, (8) im.php, (9) inbox.php, (10) join_form.php, (11) logout.php, (12) messages_inbox.php, and many other scripts.	unknown 2006-08-16	7.0	CVE-2006-4189 SECTRACK XF
Drupal -- Job Search	SQL injection vulnerability in the Job Search module (job.module) 4.6 before revision 1.3.2.1 in Drupal allows remote attackers to execute arbitrary SQL commands via a job or resume search.	unknown 2006-08-14	7.0	CVE-2006-4107 OTHER-REF BID FRSIRT SECUNIA XF
Drupal -- Bibliography Module	SQL injection vulnerability in Bibliography (biblio.module) 4.6 before revision 1.1.1.4.11 and 4.7 before revision 1.13.2.5 for Drupal allows remote attackers to execute arbitrary SQL commands via unspecified vectors.	unknown 2006-08-14	7.0	CVE-2006-4108 OTHER-REF BID FRSIRT SECUNIA
Falko Timme and Till Brehm -- SQLiteWebAdmin	PHP remote file inclusion vulnerability in tpl.inc.php in Falko Timme and Till Brehm SQLiteWebAdmin 0.1 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the conf[classpath] parameter.	unknown 2006-08-14	7.0	CVE-2006-4102 OTHER-REF FRSIRT XF
HP -- OpenView Storage Data Protector	Unspecified vulnerability in the backup agent and Cell Manager in HP OpenView Storage Data Protector 5.1 and 5.5 before 20060810 allows remote attackers to execute arbitrary code on an agent via unspecified vectors related to authentication and input validation.	unknown 2006-08-17	7.0	CVE-2006-4201 OTHER-REF HP BID FRSIRT SECTRACK SECUNIA XF
IBM -- Informix Dynamic Database Server	Buffer overflow in IBM Informix Dynamic Server (IDS) 9.40.TC7, 9.40.TC8, 10.00.TC4, and 10.00.TC5, when running on Windows, allows remote attackers to execute arbitrary code via a long username, which causes an overflow in vsprintf when displaying in the resulting error message. NOTE: this issue is due to an incomplete fix for CVE-2006-3853.	unknown 2006-08-16	7.0	CVE-2006-3854 BUGTRAQ BUGTRAQ OTHER-REF
IBM -- Websphere Application Server	Multiple unspecified vulnerabilities in IBM WebSphere Application Server before 6.1.0.1 have unspecified impact and attack vectors involving (1) "SOAP requests and responses", (2) mbean, (3) ThreadIdentitySupport, and possibly others.	unknown 2006-08-14	7.0	CVE-2006-4136 OTHER-REF AIXAPAR AIXAPAR AIXAPAR BID FRSIRT SECUNIA
IBM -- Access Support eGatherer ActiveX control	Stack-based buffer overflow in the IBM Access Support eGatherer ActiveX control before 3.20.0284.0 allows remote attackers to execute arbitrary code via a long filename parameter to the RunEGatherer method.	unknown 2006-08-18	7.0	CVE-2006-4221 OTHER-REF BID FRSIRT SECUNIA
Invision Power Services -- Invision Power Board	Unspecified vulnerability in func_topic_threaded.php (aka threaded view mode) in Invision Power Board (IPB) before 2.1.7 21013.60810.s allows remote attackers to "access posts outside the topic."	unknown 2006-08-16	7.0	CVE-2006-4155 OTHER-REF FRSIRT SECUNIA
Jason Alexander -- phNNTTP	PHP remote file inclusion vulnerability in article-raw.php in Jason Alexander phNNTTP 1.3 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the file_newsportal parameter.	unknown 2006-08-14	7.0	CVE-2006-4103 BUGTRAQ OTHER-REF BID FRSIRT SECUNIA XF
Joomla! -- Webring Component	PHP remote file inclusion vulnerability in admin.webring.docs.php in the Webring Component (com_webring) 1.0 and earlier for Joomla! allows remote attackers to execute arbitrary PHP code via a URL in the component_dir parameter.	unknown 2006-08-14	7.0	CVE-2006-4129 OTHER-REF BID FRSIRT SECUNIA
Microsoft -- Windows Help File Viewer	Multiple unspecified vulnerabilities in Microsoft Windows Help File viewer (winhlp32.exe) allow user-assisted attackers to execute arbitrary code via crafted HLP files.	2006-07-20 2006-08-14	8.0	CVE-2006-4138 BUGTRAQ BUGTRAQ BID

Microsoft -- Internet Explorer	Microsoft Internet Explorer 6.0 SP1 and possibly other versions allows remote attackers to cause a denial of service and possibly execute arbitrary code by instantiating COM objects as ActiveX controls, including (1) imskdic.dll (Microsoft IME), (2) chtskdic.dll (Microsoft IME), and (3) msoe.dll (Outlook), which leads to memory corruption. NOTE: it is not certain whether the issue is in Internet Explorer or the individual DLL files.	unknown 2006-08-16	7.0	CVE-2006-4193 BUGTRAQ BUGTRAQ BUGTRAQ OTHER-REF OTHER-REF OTHER-REF BID BID BID
Microsoft -- Internet Explorer	The Terminal Services COM object (tsuserex.dll) allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code by instantiating it as an ActiveX object in Internet Explorer 6.0 SP1 on Microsoft Windows 2003 EE SP1 CN.	unknown 2006-08-18	7.0	CVE-2006-4219 BUGTRAQ OTHER-REF BID
MODPlug -- Tracker	Multiple buffer overflows in MODPlug Tracker (OpenMPT) 1.17.02.43 and earlier and libmodplug 0.8 and earlier allow user-assisted remote attackers to execute arbitrary code via (1) long strings in ITP files used by the CSoundFile::ReadITProject function in soundlib/Load_it.cpp and (2) crafted modules used by the CSoundFile::ReadSample function in soundlib/Sndfile.cpp, as demonstrated by crafted AMF files.	unknown 2006-08-16	7.0	CVE-2006-4192 BUGTRAQ OTHER-REF FRSIRT SECUNIA XF XF
MusicBrainz -- libmusicbrainz MusicBrainz -- libmusicbrainz SVN	Multiple buffer overflows in libmusicbrainz (aka mb_client or MusicBrainz Client Library) 2.1.2 and earlier, and SVN 8406 and earlier, allow remote attackers to cause a denial of service (crash) or execute arbitrary code via (1) a long Location header by the HTTP server, which triggers an overflow in the MBHttp::Download function in lib/http.cpp; and (2) a long URL in RDF data, as demonstrated by a URL in an rdf:resource field in an RDF XML document, which triggers overflows in many functions in lib/rdfparse.c.	unknown 2006-08-17	8.0	CVE-2006-4197 BUGTRAQ BID SECTRAK SECUNIA XF XF
MVCnPHP -- MVCnPHP	Multiple PHP remote file inclusion vulnerabilities in Tony Bibbs and Vincent Furia MVCnPHP 3.0 allow remote attackers to execute arbitrary PHP code via a URL in the glConf[path_library] parameter to (1) BaseCommand.php, (2) BaseLoader.php, and (3) BaseView.php.	unknown 2006-08-16	7.0	CVE-2006-4160 OTHER-REF BID FRSIRT SECUNIA
myWebland -- miniBloggie	** DISPUTED ** PHP remote file inclusion vulnerability in cls_fast_template.php in myWebland miniBloggie 1.0 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the fname parameter. NOTE: another researcher was unable to find a way to execute code after including it via a URL. CVE analysis as of 20060816 was inconclusive.	2006-05-01 2006-08-16	7.0	CVE-2006-4163 BUGTRAQ BUGTRAQ BID
ncompress -- ncompress	The decompress function in compress42.c in (1) ncompress 4.2.4 and (2) liblwz allows remote attackers to cause a denial of service (crash), and possibly execute arbitrary code, via crafted data that leads to a buffer underflow.	unknown 2006-08-14	7.0	CVE-2006-1168 OTHER-REF DEBIAN MANDRIVA FRSIRT SECUNIA SECUNIA SECUNIA
NetCommons -- NetCommons	Cross-site scripting (XSS) vulnerability in NetCommons 1.0.8 and earlier allows remote attackers to inject arbitrary web script or HTML via unspecified vectors.	unknown 2006-08-16	7.0	CVE-2006-4165 JVN BID SECUNIA XF
Pearlabs -- Mafia MoBlog	** DISPUTED ** PHP remote file inclusion vulnerability in big.php in pearlabs mafia moblog 6 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the pathtotemplate parameter. NOTE: a third party claims that the researcher is incorrect, because template.php defines pathtotemplate before big.php uses pathtotemplate. CVE has not verified either claim, but during August 2006, the original researcher has made several significant errors regarding this bug type.	unknown 2006-08-16	7.0	CVE-2006-4156 BUGTRAQ BID
PHPMyRing -- PHPMyRing	SQL injection vulnerability in view_com.php in Nicolas Grandjean PHPMyRing 4.2.0 and earlier allows remote attackers to execute arbitrary SQL commands via the idsite parameter.	2006-08-09 2006-08-14	7.0	CVE-2006-4114 MilwOrm BID FRSIRT SECUNIA
phpPrintAnalyzer -- phpPrintAnalyzer	PHP remote file inclusion vulnerability in inc/header.inc.php in phpPrintAnalyzer 1.2 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the ficStyle parameter.	unknown 2006-08-16	7.0	CVE-2006-4164 MilwOrm BID FRSIRT XF

Ruby on Rails -- Ruby on Rails	Ruby on Rails before 1.1.5 allows remote attackers to execute Ruby code with "severe" or "serious" impact via a File Upload request with an HTTP header that modifies the LOAD_PATH variable, a different vulnerability than CVE-2006-4112.	unknown 2006-08-14	7.0	CVE-2006-4111 RUBY ON RAILS GENTOO OTHER-REF BID FRSIRT SECUNIA
Ruby on Rails -- Ruby on Rails	Unspecified vulnerability in the "dependency resolution mechanism" in Ruby on Rails 1.1.0 through 1.1.5 allows remote attackers to execute arbitrary Ruby code via a URL that is not properly handled in the routing code, which leads to a denial of service (application hang) or "data loss," a different vulnerability than CVE-2006-4111.	unknown 2006-08-14	7.0	CVE-2006-4112 RUBY ON RAILS GENTOO CERT-VN BID SECUNIA SECUNIA XF
SAP Software -- Internet Graphics Server	Buffer overflow in SAP Internet Graphics Service (IGS) 6.40 and earlier, and 7.00 and earlier, allows remote attackers to cause a denial of service (crash) or execute arbitrary code via crafted HTTP requests. NOTE: This information is based upon a vague initial disclosure. Details will be updated after the grace period has ended.	unknown 2006-08-14	7.0	CVE-2006-4133 BUGTRAQ OTHER-REF BID FRSIRT SECTRACK SECUNIA
Simple One-File Guestbook -- Simple One-File Guestbook	Simple one-file guestbook 1.0 and earlier allows remote attackers to bypass authentication and delete guestbook entries via a modified id parameter to guestbook.php.	2006-08-08 2006-08-14	7.0	CVE-2006-4122 OTHER-REF BID FRSIRT SECUNIA XF
Soft3304 -- 04WebServer	Cross-site scripting (XSS) vulnerability in Soft3304 04WebServer 1.83 and earlier allows remote attackers to inject arbitrary web script or HTML via the URL, which is not properly sanitized before it is returned in an error page, a different vulnerability than CVE-2004-1512.	unknown 2006-08-17	7.0	CVE-2006-4199 OTHER-REF BID SECUNIA XF
Soft3304 -- 04WebServer	Unspecified vulnerability in 04WebServer 1.83 and earlier allows remote attackers to bypass user authentication via unspecified vectors related to request processing.	unknown 2006-08-17	7.0	CVE-2006-4200 OTHER-REF BID SECUNIA XF
TinyWebGallery -- TinyWebGallery	PHP remote file inclusion vulnerability in TinyWebGallery 1.5 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the image parameter to (1) image.php or (2) image.php2.	unknown 2006-08-16	7.0	CVE-2006-4166 BUGTRAQ Milw0rm SECTRACK XF
Vincent Hor -- Calendarix	** DISPUTED ** PHP remote file inclusion vulnerability in cal_config.inc.php in Calendarix 0.7.20060401 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the calpath parameter. NOTE: this issue has been disputed by a third party, who says that the affected \$calpath variable is set to a constant value in the beginning of the script. CVE concurs that the initial report is invalid.	unknown 2006-08-14	7.0	CVE-2006-4135 BUGTRAQ BUGTRAQ MLIST XF
VWar -- Virtual War	SQL injection vulnerability in news.php in Virtual War (VWar) 1.5.0 and earlier allows remote attackers to execute arbitrary SQL commands via the (1) sortby and (2) sortorder parameters.	unknown 2006-08-14	7.0	CVE-2006-4141 BUGTRAQ XF
VWar -- Virtual War	SQL injection vulnerability in extra/online.php in Virtual War (VWar) 1.5.0 R14 and earlier allows remote attackers to execute arbitrary SQL commands via the n parameter.	unknown 2006-08-14	7.0	CVE-2006-4142 BUGTRAQ BID XF
WebDynamite -- ProjectButler	Multiple PHP remote file inclusion vulnerabilities in WebDynamite ProjectButler 0.8.4 allow remote attackers to execute arbitrary PHP code via a URL in the rootdir parameter to /classes/ scripts including (1) Cache.class.php, (2) Customer.class.php, (3) Performance.class.php, (4) Project.class.php, (5) Representative.class.php, (6) User.class.php, or (7) common.php.	unknown 2006-08-17	7.0	CVE-2006-4205 OTHER-REF BID XF
WEBInsta -- CMS	PHP remote file inclusion vulnerability in index.php in WEBInsta CMS 0.3.1 and possibly earlier allows remote attackers to execute arbitrary PHP code via a URL in the templates_dir parameter.	unknown 2006-08-17	7.0	CVE-2006-4196 BUGTRAQ ECHO Milw0rm BID FRSIRT

				SECUNIA
WEBInsta -- Mailing List Manager	PHP remote file inclusion vulnerability in install3.php in WEBInsta Mailing List Manager 1.3e allows remote attackers to execute arbitrary PHP code via a URL in the cabsolute_path parameter.	unknown 2006-08-17	7.0	CVE-2006-4209 BUGTRAQ OTHER-REF OTHER-REF XF
YaBB -- YaBB SE	Cross-site scripting (XSS) vulnerability in index.php in Yet another Bulletin Board (YaBB) allows remote attackers to inject arbitrary web script or HTML via the categories parameter.	unknown 2006-08-16	7.0	CVE-2006-4157 BUGTRAQ BID XF
Zen Cart -- Zen Cart	Multiple SQL injection vulnerabilities in Zen Cart 1.3.0.2 and earlier allow remote attackers to execute arbitrary SQL commands via (1) GPC data to ipn_get_stored_session, which can be leveraged to modify elements of \$_SESSION; and allow remote authenticated users to execute arbitrary SQL commands via (2) a session id within a cookie to whos_online_session_recreate, (3) the quantity field to the add_cart function, (4) an id[] parameter when adding an item to a shopping cart, or (5) a redemption code when checking out.	unknown 2006-08-17	7.0	CVE-2006-4214 OTHER-REF BID FRSIRT SECUNIA
Zen Cart -- Zen Cart	PHP remote file inclusion vulnerability in index.php in Zen Cart 1.3.0.2 and earlier, when register_globals is enabled, allows remote attackers to execute arbitrary PHP code via a URL in autoLoadConfig[999][0][loadFile] parameter.	unknown 2006-08-17	7.0	CVE-2006-4215 OTHER-REF BID FRSIRT SECUNIA
Zen Cart -- Zen Cart	Directory traversal vulnerability in Zen Cart 1.3.0.2 and earlier allows remote attackers to include and possibly execute arbitrary local files via directory traversal sequences in the typefilter parameter.	unknown 2006-08-17	7.0	CVE-2006-4218 OTHER-REF BID FRSIRT SECUNIA

[Back to top](#)

Medium Vulnerabilities				
Primary Vendor -- Product	Description	Discovered Published	CVSS Score	Source & Patch Info
ASPPlayground.NET -- ASPPlayground.NET Forum	Cross-site scripting (XSS) vulnerability in calendar.asp in ASPPlayground.NET Forum Advanced Edition 2.4.5 Unicode allows remote attackers to inject arbitrary web script or HTML via the calendarID parameter.	unknown 2006-08-17	4.7	CVE-2006-4206 BUGTRAQ XF
b0zz and Chris Vincent -- Owl Intranet Engine	Cross-site scripting (XSS) vulnerability in b0zz and Chris Vincent Owl Intranet Engine 0.90 and earlier allows remote attackers to inject arbitrary web script or HTML via unspecified vectors.	unknown 2006-08-17	4.7	CVE-2006-4211 OTHER-REF OTHER-REF FRSIRT SECUNIA
b0zz and Chris Vincent -- Owl Intranet Engine	SQL injection vulnerability in b0zz and Chris Vincent Owl Intranet Engine 0.90 and earlier allows remote attackers to execute arbitrary SQL commands via unspecified vectors.	unknown 2006-08-17	4.7	CVE-2006-4212 OTHER-REF OTHER-REF FRSIRT SECUNIA
ChaosSoft -- GeheimChaos	Multiple SQL injection vulnerabilities in GeheimChaos 0.5 and earlier allow remote attackers to execute arbitrary SQL commands via the (1) Temp_entered_login or (2) Temp_entered_email parameters to (a) gc.php, and in multiple parameters in (b) include/registrieren.php, possibly involving the (3) \$form_email, (4) \$form_vorname, (5) \$form_nachname, (6) \$form_strasse, (7) \$form_plzort, (8) \$form_land, (9) \$form_homepage, (10) \$form_bildpfad, (11) \$form_profilsichtbar, (12) \$Temp_sprache, (13) \$form_tag, (14) \$form_monat, (15) \$form_jahr, (16) \$Temp_akt_string, (17) \$form_icq, (18) \$form_msn, (19) \$form_yahoo, (20) \$form_username, and (21) \$Temp_form_pass variables.	2006-08-03 2006-08-14	5.6	CVE-2006-4118 BUGTRAQ FULLDISC BID FRSIRT SECUNIA XF
ChaosSoft -- GeheimChaos	SQL injection vulnerability in gc.php in GeheimChaos 0.5 and earlier allows remote attackers to execute arbitrary SQL commands via the Temp_entered_password parameter. NOTE: the provenance of this information is unknown; the details are obtained from third party information.	unknown 2006-08-14	5.6	CVE-2006-4119 SECUNIA XF
Drupal -- Recipe Module Drupal -- Drupal	Cross-site scripting (XSS) vulnerability in the Recipe module (recipe.module) before 1.54 for Drupal 4.6 and earlier allows remote attackers to inject arbitrary web script or HTML via unspecified vectors.	unknown 2006-08-14	5.6	CVE-2006-4120 DRUPAL DRUPAL BID FRSIRT SECUNIA

e-Zest Solutions -- PgMarket	PHP remote file inclusion vulnerability in common.inc.php in PgMarket 2.2.3, when register_globals is enabled, allows remote attackers to execute arbitrary PHP code via the CFG[libdir] parameter.	unknown 2006-08-14	5.6	CVE-2006-4115 BUGTRAQ BID XF
Hitweb -- Hitweb	PHP remote file inclusion vulnerability in genpage-cgi.php in Brian Fraval hitweb 4.2 and possibly earlier versions allows remote attackers to execute arbitrary PHP code via the REP_INC parameter.	2006-08-08 2006-08-14	5.6	CVE-2006-4113 Milw0rm BID FRSIRT SECUNIA
IBM -- Informix Dynamic Database Server	IBM Informix Dynamic Server (IDS) before 9.40.xC7 and 10.00 before 10.00.xC3 allows allows remote authenticated users to execute arbitrary commands via the (1) "SET DEBUG FILE" SQL command, and the (2) start_onpload and (3) dbexp functions.	unknown 2006-08-16	4.7	CVE-2006-3860 BUGTRAQ BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECUNIA XF XF
Lesstif -- Lesstif	The libXm library in LessTif 0.95.0 and earlier allows local users to gain privileges via the DEBUG_FILE environment variable, which is used to create world-writable files when libXm is run from a setuid program.	unknown 2006-08-14	4.9	CVE-2006-4124 OTHER-REF OTHER-REF BID FRSIRT SECUNIA XF
Lhaz -- Lhaz	Multiple stack-based buffer overflows in Lhaz before 1.32 allow user-assisted attackers to execute arbitrary code via a long filename in (1) an LHZ archive, when saving the filename during extraction; and (2) an LHZ archive with an invalid CRC checksum, when constructing an error message.	unknown 2006-08-14	5.6	CVE-2006-4116 BUGTRAQ OTHER-REF OTHER-REF FRSIRT SECUNIA XF XF
MamboXChange -- PeopleBook	PHP remote file inclusion vulnerability in param.peoplebook.php in the Peoplebook Component for Mambo (com_peoplebook) 1.0 and earlier, and possibly 1.1.2, when register_globals and allow_fopenurl are enabled, allows remote attackers to execute arbitrary PHP code via a URL in the mosConfig_absolute_path parameter.	unknown 2006-08-17	5.6	CVE-2006-4195 BUGTRAQ Milw0rm BID SECUNIA
MamboXChange -- Mambo eMail Publisher	PHP remote file inclusion vulnerability in help.mmp.php in the MMP Component (com_mmp) 1.2 and earlier for Mambo allows remote attackers to execute arbitrary PHP code via a URL in the mosConfig_absolute_path parameter.	unknown 2006-08-17	4.7	CVE-2006-4203 OTHER-REF BID FRSIRT SECUNIA XF
Matt Smith -- ReMOSitory for Mambo	PHP remote file inclusion vulnerability in admin.remository.php in the Remository Component (com_remository) 3.25 and earlier for Mambo and Joomla!, when register_globals is enabled, allows remote attackers to execute arbitrary PHP code via a URL in the mosConfig_absolute_path parameter.	unknown 2006-08-14	5.6	CVE-2006-4130 BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECUNIA XF
NetGear -- FVG318	Netgear FVG318 running firmware 1.0.40 allows remote attackers to cause a denial of service (router reset) via TCP packets with bad checksums.	unknown 2006-08-14	5.0	CVE-2006-4143 BUGTRAQ BID XF
PHP-Nuke -- AutoHTML Module	Directory traversal vulnerability in autohtml.php in the AutoHTML module for PHP-Nuke allows local users to include arbitrary files via a .. (dot dot) in the name parameter for a modload operation.	unknown 2006-08-16	4.9	CVE-2006-4190 BUGTRAQ OTHER-REF BID
PHPProjekt -- PHPProjekt	Multile PHP remote file inclusion vulnerabilities in PHPProjekt 5.1 and possibly earlier allow remote attackers to execute arbitrary PHP code via a URL in the (1) path_pre parameter in lib/specialdays.php and the (2) lib_path parameter in lib/dbman_filter.inc.php.	unknown 2006-08-17	4.7	CVE-2006-4204 OTHER-REF BID SECUNIA
See-Commerce -- See-Commerce	PHP remote file inclusion vulnerability in owimg.php3 in See-Commerce 1.0.625 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the path parameter.	unknown 2006-08-14	5.6	CVE-2006-4121 OTHER-REF BID FRSIRT

[SECUNIA](#)

Spaminator -- Spaminator	PHP remote file inclusion vulnerability in Login.php in Spaminator 1.7 and earlier allows remote attackers to execute arbitrary PHP code via a URL in the page parameter.	unknown 2006-08-16	5.6	CVE-2006-4158 OTHER-REF BID FRSIRT SECUNIA XF
SquirrelMail -- SquirrelMail	Dynamic variable evaluation vulnerability in compose.php in SquirrelMail 1.4.0 to 1.4.7 allows remote attackers to overwrite arbitrary program variables and read or write the attachments and preferences of other users.	unknown 2006-08-11	4.7	CVE-2006-4019 SQUIRRELMAIL SQUIRRELMAIL FRSIRT SECUNIA BUGTRAQ BUGTRAQ FULLDISC MLIST OTHER-REF BID OSVDB SECTrack SECUNIA XF
Symantec Veritas -- Backup Exec	Multiple heap-based buffer overflows in Symantec VERITAS Backup Exec for Netware Server Remote Agent for Windows Server 9.1 and 9.2 (all builds), Backup Exec Continuous Protection Server Remote Agent for Windows Server 10.1 (builds 10.1.325.6301, 10.1.326.1401, 10.1.326.2501, 10.1.326.3301, and 10.1.327.401), and Backup Exec for Windows Server and Remote Agent 9.1 (build 9.1.4691), 10.0 (builds 10.0.5484 and 10.0.5520), and 10.1 (build 10.1.5629) allow remote attackers to cause a denial of service (application crash) and possibly execute arbitrary code via a crafted RPC message.	unknown 2006-08-14	4.2	CVE-2006-4128 BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECTrack SECUNIA XF
Wheatblog -- Wheatblog	PHP remote file inclusion vulnerability in includes/session.php in Wheatblog (wB) 1.1 and earlier, when register_globals is enabled, allows remote attackers to execute arbitrary PHP code via a URL in the wb_class_dir parameter.	unknown 2006-08-17	5.6	CVE-2006-4198 BUGTRAQ SECWATCH Milw0rm SOURCEFORGE BID XF
XMB Software -- Extreme Message Board	Directory traversal vulnerability in memcp.php in XMB (Extreme Message Board) 1.9.6 and earlier allows remote attackers to include and execute arbitrary local files via directory traversal sequences in the langfilenew parameter, as demonstrated by injecting PHP sequences into an Apache HTTP Server log file, which is then included by header.php.	unknown 2006-08-16	5.6	CVE-2006-4191 BUGTRAQ ALTERVISTA Milw0rm BID SECUNIA XF

[Back to top](#)

Low Vulnerabilities				
Primary Vendor -- Product	Description	Discovered Published	CVSS Score	Source & Patch Info
Andreas Kansok -- phPay	nu_mail.inc.php in Andreas Kansok phPay 2.02 and 2.02.1, when register_globals is enabled, allows remote attackers to use the server as an open mail relay via modified mail_text2, user_row[5], nu_mail_1, and shop_mail parameters. NOTE: some of these details are obtained from third party information.	unknown 2006-08-17	2.3	CVE-2006-4210 OTHER-REF BID SECUNIA XF
Apache Software Foundation -- Apache	Apache 2.2.2, when running on Windows, allows remote attackers to read source code of CGI programs via a request that contains uppercase (or alternate case) characters that bypass the case-sensitive ScriptAlias directive, but allow access to the file on case-insensitive file systems.	2006-08-08 2006-08-14	1.9	CVE-2006-4110 BUGTRAQ BID FRSIRT SECUNIA
Arcsoft -- MMS Composer	ArcSoft MMS Composer 1.5.5.6 and possibly earlier, and 2.0.0.13 and possibly earlier, allow remote attackers to cause a denial of service (resource exhaustion and application crash) via WAPPush messages to UDP port UDP 2948.	unknown 2006-08-14	2.3	CVE-2006-4132 BUGTRAQ FULLDISC OTHER-REF OTHER-REF OTHER-REF BID SECUNIA

Blursoft -- Blur6ex	Cross-site scripting (XSS) vulnerability in blursoft blur6ex 0.3 allows remote attackers to inject arbitrary web script or HTML via a comment title.	unknown 2006-08-14	2.3	CVE-2006-4106 BUGTRAQ BID
DConnect -- DConnect Daemon	The dc_chat function in cmd.dc.c in DConnect Daemon 0.7.0 and earlier allows remote attackers to cause a denial of service (application crash) by sending a client message before providing the nickname, which triggers a null pointer dereference.	unknown 2006-08-14	2.3	CVE-2006-4126 BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECTrack SECUNIA XF
DConnect -- DConnect Daemon	Multiple format string vulnerabilities in DConnect Daemon 0.7.0 and earlier allow remote administrators to execute arbitrary code via format string specifiers that are not properly handled when calling the (1) privmsg() or (2) pubmsg functions from (a) cmd.user.c, (b) penalties.c, or (c) cmd.dc.c.	unknown 2006-08-14	3.4	CVE-2006-4127 BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECTrack SECUNIA XF
Drupal -- Bibliography Module	Cross-site scripting (XSS) vulnerability in Bibliography (biblio.module) 4.6 before revision 1.1.1.4.11 and 4.7 before revision 1.13.2.5 for Drupal allows remote attackers to inject arbitrary web script or HTML via unspecified vectors.	unknown 2006-08-14	2.3	CVE-2006-4109 DRUPAL BID FRSIRT SECUNIA
Fill Threads Database -- Fill Threads Database	Cross-site scripting (XSS) vulnerability in Fill Threads Database (FTD) 3.7.3 allows remote attackers to inject arbitrary web script or HTML via the (1) search field or (2) an e-mail message.	unknown 2006-08-14	2.3	CVE-2006-4105 BUGTRAQ BID SECTrack XF
Gallery Project -- Gallery	Unspecified vulnerability in the stats module in Gallery 1.5.1-RC2 and earlier allows remote attackers to obtain sensitive information via unspecified attack vectors, related to "two file exposure bugs."	unknown 2006-08-16	2.3	CVE-2006-4030 OTHER-REF DEBIAN BID FRSIRT SECUNIA SECUNIA
High Availability Linux Project -- Heartbeat	The heartbeat subsystem in High-Availability Linux before 1.2.5 and 2.0 before 2.0.7 allows remote attackers to cause a denial of service (crash) via a crafted heartbeat message.	unknown 2006-08-16	2.3	CVE-2006-3121 OTHER-REF OTHER-REF DEBIAN BID
HP -- HP-UX	Unspecified vulnerability in HP-UX B.11.00, B.11.11 and B.11.23, when running in trusted mode, allows local users to cause a denial of service via unspecified vectors.	unknown 2006-08-16	1.6	CVE-2006-4187 HP BID SECTrack
HP -- HP-UX	Unspecified vulnerability in the LP subsystem in HP-UX B.11.00, B.11.04, B.11.11, and B.11.23 allows remote attackers to cause a denial of service via unknown vectors.	unknown 2006-08-16	2.3	CVE-2006-4188 HP BID SECTrack SECUNIA
IBM -- Informix Dynamic Database Server	IBM Informix Dynamic Server (IDS) allows remote authenticated users to create and overwrite arbitrary files via the (1) LOTOFILE and (2) trl_tracefile_set functions, and the (3) "SET DEBUG FILE" commands.	unknown 2006-08-16	1.4	CVE-2006-3859 BUGTRAQ BUGTRAQ OTHER-REF
IBM -- Websphere Application Server	IBM WebSphere Application Server before 6.1.0.1 allows attackers to obtain sensitive information via unspecified vectors related to (1) the log file, (2) "script generated syntax on wsadmin command line," and (3) traces.	unknown 2006-08-14	2.3	CVE-2006-4137 OTHER-REF AIXAPAR AIXAPAR AIXAPAR BID FRSIRT SECUNIA
IBM -- Websphere Application Server	Multiple unspecified vulnerabilities in IBM WebSphere Application Server before 6.0.2.13 have unspecified vectors and impact, including (1) an "authority problem" in ThreadIdentitySupport as identified by PK25199, and "Potential security exposure" issues as identified by (2) PK22747, (3) PK24334, (4) PK25740, and (5) PK26123.	unknown 2006-08-18	2.3	CVE-2006-4222 OTHER-REF FRSIRT SECUNIA

ImageMagick -- ImageMagick	Integer overflow in the ReadSGIImage function in sgi.c in ImageMagick before 6.2.9 allows user-assisted attackers to cause a denial of service (crash) and possibly execute arbitrary code via large (1) bytes_per_pixel, (2) columns, and (3) rows values, which trigger a heap-based buffer overflow.	unknown 2006-08-15	1.9	CVE-2006-4144 BUGTRAQ OTHER-REF BID SECUNIA
IPCheck -- Server Monitor	Directory traversal vulnerability in IPCheck Server Monitor 5.3.2.609 and earlier allows remote attackers to read arbitrary files via modified .. (dot dot) sequences in the URL, including (1) "%2f" (encoded "/" slash), "%2f" (multiple dot), and "%25c." (double-encoded "\" backslash).	unknown 2006-08-14	2.3	CVE-2006-4140 BUGTRAQ BID FRSIRT SECTrack SECUNIA XF
Linux -- Linux kernel	Race condition between the kfree_skb and __skb_unlink functions in the socket buffer handling in Linux kernel 2.6.9, and possibly other versions, allows remote attackers to cause a denial of service (crash), as demonstrated using the TCP stress tests from the LTP test suite.	unknown 2006-08-15	2.7	CVE-2006-2446 REDHAT OTHER-REF
MojoScripts -- mojoGallery	Cross-site scripting (XSS) vulnerability in admin.cgi in mojoscripts.com mojoGallery allows remote attackers to inject arbitrary web script or HTML via the username parameter. NOTE: the provenance of this information is unknown; the details are obtained from third party information.	unknown 2006-08-11	2.3	CVE-2006-4087 FRSIRT SECUNIA
MojoScripts -- mojoGallery	Cross-site scripting (XSS) vulnerability in admin.cgi in mojoscripts.com mojoGallery allows remote attackers to inject arbitrary web script or HTML via "password input."	unknown 2006-08-14	2.3	CVE-2006-4104 BUGTRAQ BID FRSIRT SECUNIA
Novell -- eDirectory	Unspecified vulnerability in the NCPENGINE in Novell eDirectory 8.7.3.8 allows local users to cause a denial of service (CPU consumption) via unspecified vectors, as originally demonstrated using a Nessus scan.	unknown 2006-08-16	2.3	CVE-2006-4185 NOVELL BID SECTrack SECUNIA
Novell -- eDirectory	The iManager in eMBoxClient.jar in Novell eDirectory 8.7.3.8 writes passwords in plaintext to a log file, which allows local users to obtain passwords by reading the file.	unknown 2006-08-16	1.6	CVE-2006-4186 OTHER-REF BID SECTrack SECUNIA
SAP Software -- Internet Graphics Server	Unspecified vulnerability related to a "design flaw" in SAP Internet Graphics Service (IGS) 6.40 and earlier and 7.00 and earlier allows remote attackers to cause a denial of service (service shutdown) via certain HTTP requests. NOTE: This information is based upon a vague initial disclosure. Details will be updated after the grace period has ended.	unknown 2006-08-14	2.3	CVE-2006-4134 BUGTRAQ FULLDISC OTHER-REF BID FRSIRT SECTrack SECUNIA XF
ScatterChat -- ScatterChat	The cryptographic module in ScatterChat 1.0.x allows attackers to identify patterns in large numbers of messages by identifying collisions using a birthday attack on the custom padding mechanism for ECB mode encryption.	unknown 2006-08-17	1.9	CVE-2006-4021 BUGTRAQ SCATTERCHAT SCATTERCHAT
Skippy.net -- WP-DB Backup Plugin for Wordpress	Directory traversal vulnerability in wp-db-backup.php in Skippy WP-DB-Backup plugin for WordPress 1.7 and earlier allows remote authenticated users with administrative privileges to read arbitrary files via a .. (dot dot) in the backup parameter to edit.php.	unknown 2006-08-17	2.3	CVE-2006-4208 BUGTRAQ OTHER-REF OTHER-REF BID FRSIRT SECUNIA XF
SmartLine -- DeviceLock	SmartLine DeviceLock before 5.73 Build 305 does not properly enforce access control lists (ACL) in raw mode, which allows local users to bypass NTFS controls and obtain sensitive information.	unknown 2006-08-16	2.3	CVE-2006-4184 BUGTRAQ OTHER-REF BID SECUNIA XF
Spidey Blog -- Spidey Blog Script	SQL injection vulnerability in proje_goster.php in Spidey Blog Script 1.5 and earlier allows remote attackers to execute arbitrary SQL commands via the pid parameter.	unknown 2006-08-17	2.3	CVE-2006-4202 Milw0rm BID SECUNIA

Sun -- Solaris	The <code>squeue_drain</code> function in Sun Solaris 10, possibly only when run on CMT processors, allows remote attackers to cause a denial of service ("bad trap" and system panic) by opening and closing a large number of TCP connections ("heavy TCP/IP loads"). NOTE: the original report specifies the function name as "drain_squeue," but this is likely incorrect.	unknown 2006-08-14	2.7	CVE-2006-4117 SUNALERT FRSIRT SECUNIA
Sun -- Solaris	Race condition in Sun Solaris 10 allows attackers to cause a denial of service (system panic) via unspecified vectors related to <code>ifconfig</code> and either <code>netstat</code> or <code>SNMP</code> queries.	unknown 2006-08-14	2.7	CVE-2006-4139 SUNALERT FRSIRT SECTrack SECUNIA
Webligo -- BlogHoster	Cross-site scripting (XSS) vulnerability in Webligo BlogHoster 2.2 allows remote attackers to inject arbitrary web script or HTML via the "From: part of the comment post," probably involving the nickname parameter to <code>previewcomment.php</code> .	unknown 2006-08-11	2.3	CVE-2006-4090 BUGTRAQ BID FRSIRT OSVDB SECUNIA XF
XennoBB -- XennoBB	Directory traversal vulnerability in the <code>avatar_gallery</code> action in <code>profile.php</code> in XennoBB 2.1.0 and earlier allows remote attackers to read arbitrary files via a <code>..</code> (dot dot) in the category parameter.	unknown 2006-08-16	2.3	CVE-2006-4161 BUGTRAQ OTHER-REF BID SECUNIA XF

[Back to top](#)